

SILO-KING[®]

APPLICATORS



SIDEKICK

CAPACITY

Without extension - 1.56 cu. ft. (40 lbs. of Silo-King[®])

With extension - 1.85 cu. ft. (80 lbs. of Silo-King[®])

DIMENSIONS

Standard - 20" x 17" x 19"

With leg kit - 20" x 17" x 19.5"

With leg kit to fit HD blower - 20" x 17" x 48"



DAVID

CAPACITY

Standard - 4.5 cu. ft. (160 lbs. of Silo-King[®])

DIMENSIONS

Standard - 18" x 29" x 33"

With leg kit to fit HD blower - 18" x 29" x 45"



GOLIATH

CAPACITY

Standard - 9.36 cu. ft. (280 lbs. of Silo-King[®])

DIMENSIONS

Standard - 46" x 19.5" x 31.5"



GANDY[®] P45

CAPACITY

Without extension - 1 cu. ft. (40 lbs. of Silo-King[®])

With extension - 2 cu. ft. (80 lbs. of Silo-King[®])

DIMENSIONS

Without extension - 15" x 14" x 21"

With extension - 15" x 14" x 30"

SILO-KING[®]

CONTROLLERS



MC-10

FEATURES

- Cab-based simple rate control
- Rate chart with 1-10 dial
- LED indicator light
- Blower on/off switch



SM-10

FEATURES

- Cab-based rate adjustment
- Digital display monitor
- Simple calibration
- Three resettable usage monitors
- Blower RPM monitor

OPTIONAL FEATURES

- Bin level sensor
- Variable rate bale speed sensor
(for large/small square bales)
- Photo eyes



ISOmod

FEATURES

- Cab-based rate adjustment
- Digital display monitor
- Simple calibration
- Three resettable usage monitors
- Blower RPM monitor
- Works with ISOBUS-compatible terminals
- Auto-Cal to determine harvest rate
- Product Default selections
- Live mass/moisture readings (JD compatible, more coming)